

ICPS-1224-K

24 埠 10/100TX + 2 埠 10/100/1000T SFP + 24 PoE 供電 複合埠
24 埠 PoE 供電型工業乙太網路交換機



- 符合 IEEE 802.3at+ PoE 電力線供電標準，單埠輸出高達 30W
- 符合工業安全規範標準
- 支援 26 埠 Non-Blocking 無阻塞設計
- 支援 store and forward 存儲轉發設計
- AC 電壓輸入設計 110V~240V
- 適用環境：安防領域、戶外監控、工業自動化、工業視覺檢測



OVERVIEW

萬東科技 ICPS-1224-K 提供 24 埠 100M 端口，包含 2 port 10/100/1000 M RJ-45 端口以及 2 port 1000M 光纖複合埠，並支援 SFP 標準界面，其中 1~24 埠支持 POE (power over Ethernet) 符合 IEEE802.3 at /IEEE 802.3 at+，最高輸出每埠 30W，可應用於多數 PTZ IP-cam 以及 Speed Dome 需求。

ICPS-1224-K 採 Non-Blocking 無阻塞設計，確保在各種狀況下能全速傳輸，同時每埠最高可提供 200Mbps 雙向傳輸速率，提供足夠的帶寬處理能力，確保網路可長時間並且穩定使用，是提升網路性能的最佳方案。

ICPS-1224-K 可與戶外無線接入點(WIFI-AP)及 Speed Dome/IP-CAM 等設備連接，並可應用於安防科技、戶外監控、工業自動化、工業視覺檢測、太陽能發電應用等環境。

ICPS-1224-K 支援寬溫設計，符合-20~60 度操作溫度，可長時間安裝於戶外機箱，是最佳工業級網路交換機方案。

FEATURES & BENEFITS

- 系統介面 / 效能
 - RJ-45 埠支援 Auto MDI/MDI-X 功能
 - 嵌入式 24-埠 PoE 供電模組
 - 存儲轉發系統架構
 - 背板頻寬 (Switching Fabric): 11Gbps
 - 16K MAC 網路地址表
- 工溫設計(-20°C~60°C)
- 強化設計，符合 IP-30 保護
- 電壓輸入交流 110V-240V
- 符合工業用檢磁及安全規範
- 支援極性保護，過電流保護

SPECIFICATION

Hardware Specification		
IEEE Standards	IEEE802.3 10Base-T Ethernet IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3z Gigabit fiber IEEE802.3x Flow Control and Back Pressure	10/100/1000T/SFP Combo port: 2 x RJ-45 + 2 x 100/1000 SFP socket
Switch Architecture	Back-plane (Switching Fabric): 5.6Gbps	Network Cable 10Base-T: 2-pair UTP/STP Cat. 3, 4, 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 1000Base-TX: 2-pair UTP/STP Cat. 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m)
Transfer Rate	14,881pps for Ethernet port 148,810pps for Fast Ethernet port 1,488,100pps for Gigabit Fiber Ethernet port	
MAC Address	16K MAC address table	Optical Fiber Distance: Multi mode: 0 to 5 km, 1300 nm (50/125 μm, 800 MHz*km) 0 to 4 km, 1300 nm (62.5/125 μm, 500 MHz*km) Single mode:
Connectors	10/100TX: 24 x ports RJ-45 with Auto MDI/MDI-X function	

Datasheet Version 1.2

	0 to 40 km, 1310 nm (9/125 μm, 3.5 PS/(nm*km)) 0 to 80 km, 1550 nm (9/125 μm, 19 PS/(nm*km)) Min. TX Output: Multi mode: -20 dBm Single mode: 0 to 40 km, -5 dBm; 0 to 80 km, -5 dBm Max. TX Output: Multi mode: -14 dBm Single mode: 0 to 40 km, 0 dBm; 0 to 80 km, 0 dBm Sensitivity: -36 to -32 dBm(SM); -34 to -30(MM)	Storage Temperature	-40°C~85°C / -40°F~185°F
Protocol	CSMA/CD	Case Dimension	IP-30, 440 (W) x 200 (D) x 44 (H) mm
PoE pin assignment	RJ-45 port # 1~#24 support IEEE 802.3at+ Endpoint, Alternative A mode. Per port provides up to 30W Positive (VCC+): RJ-45 pin 3,6. Negative (VCC-): RJ-45 pin 1,2.	Weight	2000 g
LED	Per unit: Power 1 (Green), Power 2 (Green), Fault (Red), 24 port 10/100: Link/Activity (Green), Full duplex/Collision (Yellow) SFP port: LNK/ACT(Green), 1000T : LNK/ACT(Green), 1000M(Green)	Fan Number	2
Power Supply	PoE input 48V~56VDC, Ethernet Data input 110V~240VAC;	Installation	Wall mount
Overload current protection	Present	MTBF	190288 hrs
Operating Humidity	5% ~ 95% (Non-condensing)	EMI & EMS	FCC Class A, CE EN61000-4-2, CE EN61000-4-3, CE EN61000-4-4, CE EN61000-4-5, CE EN61000-4-6, CE EN61000-4-8, CE EN61000-4-11, CE EN61000-6-2, CE EN61000-6-4
Operating Temperature	Standard: -20°C~60°C / -4°F~140°F	Stability Testing	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)
		Power Consumption	9.86 W (no PoE load) for Ethernet data at full load
		PoE Power Budget	480W
		Warranty	3 years

*Future Release
**Optional

ORDERING INFORMATION

- **ICPS-1224-K**
24 10/100TX + 2 10/100/1000T SFP Combo w/24 PoE Hi power Unmanaged Industrial Switch ; Input 110V~240V AC - 20°C to 60°C

OPTIONAL ACCESSORIES

Mini GBIC (SFP)

- | | |
|--|--|
| ■ 8330-162 MINI GBIC 1000SX (LC/0.5km) Transceiver | ■ 8330-188 LTSFP-1000BX-10KM Transceiver (WDM 1310) |
| ■ 8330-163 MINI GBIC 1000SX2 (LC/2km) Transceiver | ■ 8330-189 LTSFP-1000BX-10KM Transceiver (WDM 1550) |
| ■ 8330-165 MINI GBIC 1000LX (LC/10km) Transceiver | ■ 8330-186 LTSFP-1000BX-20KM Transceiver (WDM 1310) |
| ■ 8340-0591 MINI GBIC 1000LHX (LC/40km) Transceiver | ■ 8330-187 LTSFP-1000BX-20KM Transceiver (WDM 1550) |
| ■ 8330-166 MINI GBIC 1000XD (LC/50km) Transceiver | ■ 8330-180 LTSFP-1000BX-40KM Transceiver (WDM 1310) |
| ■ 8330-169 MINI GBIC 1000XD (LC/60km) Transceiver | ■ 8330-182 LTSFP-1000BX-40KM Transceiver (WDM 1550) |
| ■ 8330-167 MINI GBIC 1000ZX (LC/80km) Transceiver | ■ 8330-181 LTSFP-1000BX-60KM Transceiver (WDM 1310) |
| ■ 8330-170 MINI GBIC 1000EZ (120km) Transceiver | ■ 8330-183 LTSFP-1000BX-60KM Transceiver (WDM 1550) |
| ■ 8330-168 MINI GBIC 1000T (100m) Transceiver | ■ 8330-184 LTSFP-1000BX-80KM Transceiver (WDM 1490) |
| ■ 8330-061 100Base LX 30KM, Single-mode, LC Transceiver | ■ 8330-185 LTSFP-1000BX-80KM Transceiver (WDM 1550) |
| ■ 8330-060 100Base FX 2KM, Multi-mode, LC Transceiver | |

WanDong Technology Co.,Ltd..
www.wandong.com.tw
shsh0963@gmail.com

© 2021 Copyright WanDong Technology Co.,Ltd. all rights reserved.
 The revise authority rights of product specifications belong to WanDong Technology Co.,Ltd.
 WanDong may make changes to specification and product descriptions at anytime, without notice.